



INTERNAL LOAD BEARING PARTITION (TO PROVIDE MINIMUM 40 dB AIRBORNE SOUND RESISTANCE):

- TWO LAYERS OF 12.5mm PLASTERBOARD WITH 3mm SKIM COAT - ALL JOINTS TO BE TAPED AND SEALED. SEAL ALL JUNCTIONS WITH INTUMESCENT SEALANT
- 90mm LIGHT STEEL FRAME SYSTEM WITH MINERAL WOOL INSULATION (0.038 THERMAL CONDUCTIVITY)
- TWO LAYERS OF 12.5mm PLASTERBOARD WITH 3mm SKIM COAT - ALL JOINTS TO BE TAPED AND SEALED.

SKIRTING 25x100mm PENCIL ROUNDED PAINTED MDF

1200 GAUGE DPM AND DPC TO BE WELL LAPPED

1.2mm X 200mm STEEL PLATE FIXED TO STUDS WITH NOMINAL 45mm PERIMETER INSULATION

SOLID GROUTING

BEAM BLOCK FLOOR TO SE DESIGN

CONCRETE OVERSITE

Rev.	Date	Description	Init.
B	26/01/2017	General Build up Amendments	CM
A	14/12/2016	General Build up Amendments	EHG/DW

Client

HADFRAME

Project Title

HADFRAME SYSTEM

Drawing Title
3B5P
INTERNAL WALL AND GROUND FLOOR JUNCTION

Cad File	Sheet Size	Scale
1485_DETAILS SET A3	A3	1:5
Drawn by	Drawing Date	Approved by
EHG	AUG 2016	DW
Project No.	Drawing No.	Revision
1485	D01A-5	B

This drawing is property of Daria Wong Architects © and must not be copied or otherwise reproduced. All dimensions must be checked on site before commencing work. No dimensions to be scaled from this drawing. This drawing was produced using AutoCad LT.

PRELIMINARY